

KM-1815 Specifications

basic specifications:

Configuration:	Desktop Digital Multifunctional with Standard 250 Sheet Paper Drawer Plus 50 Sheet Multi-Purpose Tray, 96MB RAM Memory, Scan Once Print Many and Electronic Sort. Standard Printing and Color Scan to E-Mail. Standard Network Interface. Optional 50 Sheet Document Processor and Paper Handling.
Resolution:	600 x 600 DPI/ 256 Levels; Fast 1200 Print Resolution (1800 x 600), 2400 x 600 DPI w/ KIR
Copier Memory:	Standard 96MB RAM upgradeable to 320MB via 100 Pin DIMMS (1 slot).
Magnification:	Full Size, Auto Magnification, Plus 50-200% Zoom in 1% Increments
Electrical Requirements:	120V, 60Hz, 7.8A
Dimensions:	(w/o DP) 19.5"W x 16.6"D x 15.2"H (w/ DP) 19.5"W x 16.6"D x 17.9"H
Weight:	32.0 lbs
Max Monthly Volume:	15,000 Pages per Month

output speeds:

Warm-Up Time:	30 Seconds
First Print Out:	8 Seconds
First Copy Out:	10 Seconds
Pages Per Minute:	18 Letter, 15 Legal

paper supply:

Standard Paper Sources:	250 Sheet Drawer, 50 Sheet MPT
Drawer Paper Size:	5.5" x 8.5" - 8.5" x 14"
MPT Paper Size:	5.5" x 8.5" - 8.5" x 14"
Std / Max Paper Capacity:	300 / 550
Paper Weight:	16-28 lb bond via Paper Drawers, 16 lb Bond -90 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Envelopes

copy functions:

Imaging Modes:	Auto, Text, Photo, Text / Photo, Manual, ECO
Continuous Copy:	Up to 999, Auto Reset to 1
Additional Features:	Auto Magnification and Paper Select, Scan Once Print Many, Electronic Sort, 2 in 1, 4 in 1, ECO Mode

paper handling options:

document processor: DP-100

Type:	Automatic Document Feeder
Acceptable Originals:	5.5" x 8.5" - 8.5" x 14"
Capacity:	50 Sheet ADF
Speed:	18 Originals per Minute
Paper Weight:	13- 32 lb Bond
Dimensions/Weight:	17.9"W x 13"D x 3.7"H / 5.1 lbs.

paper drawers: PF-17

Paper Capacity:	250 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11" - 8.5" x 14"
Dimensions / Weight:	14.9"W x 14.7"D x 3.1"H / 4.8 lbs

additional options:

System Memory:	64, 128, 256 MB DIMM Memory
----------------	-----------------------------

connectivity: standard print/scan:

PRINT:

Controller:	Embedded PowerPC750/ 300 MHz Controller
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL3 (PS3), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL XL/5e and KPDL, 1 Bitmap Font
Windows™ OS Compatibility:	Windows™ 95/98/Me/NT4.x/2000/XP/2003
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100BaseTX, Parallel IEEE1284, High Speed USB 2.0
Supported Protocols:	TCP/IP, AppleTalk, NetBEUI
Driver:	KX Driver for Windows™, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver
Utilities:	KM-NET Viewer, KM-NET Clients, PDF Direct Print, Quick Setup Tool, Kyocera Command Center, PRESCRIBE Utilities

COLOR SCAN TO E-MAIL

Resolution:	200, 300, 400, 600 DPI
Scan Speed:	Up to 18 Sheets Per Minute (Mono) Up to 5 Sheets Per Minute (Color)
File Formats:	Mono: PDF, TIFF Color: PDF, JPEG
Connectivity:	Standard 10/100BaseTX
Supported Protocols:	TCP/IP
Scanning Features:	Scan to E-Mail (minimum software requirements apply)
Additional Features:	8 One Touch Destinations, Scan Color Select



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com/us.
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters:
225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
© 2004 Kyocera Mita America, Inc.



www.kyoceramita.com/us